

YTELSESERKLÆRING

Nr: 401

| | | | | |
|---|---|---|---------------|------------------|
| 1 | Unik identifikasjonskode av produkttype: | | | |
| | | <ul style="list-style-type: none"> • Flügger Wet Seal, Wall Seal och All Seal • + artikkelnummer og produksjonsserie på emballasjen | | |
| 2 | Tiltenkt bruk: | | | |
| | | <ul style="list-style-type: none"> • EN 15651 Fugemasser til fuging innendørs og utendørs | | |
| 3 | Produsent: | | | |
| | | <ul style="list-style-type: none"> • FLÜGGER Grönkullen SE-517 81 Bollebygd. www.flugger.se | | |
| 4 | AVCP-system: | | | |
| | | <ul style="list-style-type: none"> • System 3 for reaction for fire | | |
| 5 | Harmonisert standard: | | | |
| | | <ul style="list-style-type: none"> • EN 15651-1:2012 Sealants for non-structural use in joints in buildings and pedestrian walkways- • Part 1: Sealants for façade elements. • Part 2: Sealants for glazing • Part 3: Sealants for sanitary joints • • SKZ- TeCona A GmbH NB 1213 • IFT Rosenheim GmbH NB 0757 | | |
| 6 | Erklært ytelse: | | | |
| | | | | |
| | | Wet Seal | Wall Seal | All Seal |
| | | EN15651-1 | EN15651-1 | EN15651-1 |
| Type | | F-EXT-INT | F-INT | F-EXT-INT-CC |
| Class | | 25LM | | 25HM |
| | | | | |
| Reaction to fire | | Class E | NPD | Class E |
| Release dangerous chemicals | | NPD | NPD | NPD |
| Resistance to flow | | ≤ 3 mm | ≤ 3 mm | ≤ 3 mm |
| Loss of volume | | ≤ 10% | NPD | ≤ 10% |
| Elongation at break | | ≥ 25% | ≥ 25% | |
| Tensile properties at maintained extension after water immersion | | | | NF |
| Tensile properties (secant modulus) for use in cold climate areas (-30°C) | | | | ≤ 0,9 mPa |
| Tensile properties at maintained extension for use in cold climate areas (-30°C) | | | | NF |
| Durability | | | | Pass |
| | | | | |
| | | EN15651-2 | | |
| Type | | G | | |
| Class | | 25LM | | |
| | | | | |
| Elastic recovery | | ≥ 70 % | | |
| Secant modulus at 23°C (N/mm ²) | | ≤ 0,4 | | |
| Secant modulus at -20°C (N/mm ²) | | ≤ 0,6 | | |
| Adhesion/cohesion after exposure to heat, water and artificial light | | NF | | |
| Resistance to compression (N/mm ²) | | 0,26 | | |
| | | | | |
| | | | | |
| | | | | |

| | | | |
|--|------------------|------------------|--------------------|
| | | | |
| | Wet Seal | Wall Seal | All Seal |
| | EN15651-3 | | |
| Type | S | | |
| Class | XS1 | | |
| | | | |
| Tensile properties at maintained extension | NF | | |
| Adhesion/cohesion at variable temperatures | NF | | |
| Adhesion /cohesion at maintained extension after water immersion | NF | | |
| | | | |
| Conditioning | Method A | Method A | Procedure B |
| Substrate | Aluminium | Aluminium | Mortar M1 |
| | Mortar | Mortar | |
| | Glass | | |

7

Ytelsen til produktet som er identifisert ovenfor er i samsvar med settet av erklært ytelse. Denne ytelseserklæringen er utstedt i henhold til forordning (EU) nr. 305/2011 under produsentens eneansvar som angitt ovenfor.

Signert for og på vegne av produsenten av:

Navn:

- **Anders Frisk**

Stilling:

- **R&D Specialist, Documentation**

Sted:

- **Bollebygd**

Dato 2014.11.07

-

Signatur: