

Colour Chips

Product properties

Colored Vinyl Chips for Floors. Recommended for premises with high functional requirements that are exposed to light traffic, use-related wear, and some soiling.

- Colored vinyl chips
- Non-slip surface
- Extra durable surface



Product use

Used together with Ep-V Floor paint.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Prime absorbent and porous surfaces with Epoxy Floor Paint diluted with 20 % water.
If there has been more than 24 hours between treatments, the surface must be sanded matt.
Scatter color chips on the wet surface, 20-150 g/m².
After drying, vacuum the floor for color chips that have not attached to the substrate.
Finish the treatment with EP-V varnish to obtain a robust surface.

Application

Brush or roller.
Condensation during drying/curing must not occur.
Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Glossy extra non-slip surface.
Withstands cleaning including spot cleaning with mild, non-abrasive detergents, soft brush, water, and cloth.
Avoid cleaning methods and machines that scratch or damage the painted surface.
Exercise care in loading the surface until the paint is fully cured.
The surface can be taken into use after 10 hours.

Technical Data

Current TDS Version

November 2023

Replaces TDS Version

August 2022