

Colour Sample Transparent

Product properties

Transparent color sample to help you make a color choice.

- Transparent
- Colour sample
- Semi-matt

Product use

Used for color selection inside and outside.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

New wood is dusted off.

Marks and stains are sanded off.

Previously stained wood is cleaned with Flügger Natural Wood Wood Cleaner.

Dry afterwards with a hard-wrung cloth.

The color sample is placed on an object of suitable size.

Avoid treatment on the substrate to be painted to avoid marking in the finished result.

Use a movable object so that the colour can be viewed from different angles and light incidence.

Application

Brush.

Stir thoroughly before and during use.

Apply in an even, thin layer along the length of the wood.

Avoid overlaps.

Condensation during drying/curing must not occur.

Please note that the color depends on the wood's own color and the number of applications.

The more applications, the darker the color.

Expected result

Uniform stained surface.

Please note!

Please note that minor nuance differences between color card, color sample and final result may occur depending on product choice, gloss, structure, lighting and viewing angle.

Can only be used as a color sample and not as a finishing treatment.



Environmental information

Remove as much paint as possible before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost free and tightly closed

Technical Data

Product Type	Acrylic paint;Colour sample
Gloss	Semi Matte
Density (kgs/l)	1.02
Solids Weight %	22
Solids Vol. %	20
Nominal spreading rate (m ² /ltr.)	15
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Water and soap

Current TDS Version

October 2023

Replaces TDS Version

July 2022