

Stain Varnish

Product properties

Black lacquer stain for combined dyeing and varnishing of wood. Provides a very robust and durable surface. Available in semi-gloss and matt.

Product use

Use it indoors on, fx, table tops, furniture and other wooden inventory.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Treatment

Clean previously painted surfaces with Natural Wood Wood Cleaner. Previously varnished surfaces must be sanded matt. Wipe with a hard-wrung cloth.

Application

Brush or roller.
Stir before and during use.
Apply lacquer stain twice at 24 hour intervals.
Sand lightly between each application.
Condensation during drying / curing must not form.
Always apply test treatments to check and accept the adhesion and results.

Expected result

Colored surface which appears saturated and uniform in gloss and finish. The durability of the surface depends on the wood quality, structure, application and exposure.

Please note!

Oil-saturated cloths can ignite spontaneously.
Saturated with water or destroyed.

Environmental information

Remove as much paint from tools as possible before cleaning.
Bring remains of fluent paint to the local recycling centre.
Minimize your paint waste by pre-estimating how much paint you need.
Keep the leftover paint for future use so you can effectively reduce the environmental impact.



Storage: Cool, frost free and tightly closed

Protection equipment: Painting: eye protection, gloves. Sanding: respiratory protection.

Technical Data

Gloss	Matte;Semi Gloss
Density (kgs/l)	0.90
Solids Weight %	45
Nominal spreading rate (m ² /ltr.)	10
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	12
Recoatable at 20° C, 60 % RH (Hours)	24
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Brush Cleaner

Current TDS Version

March 2024

Replaces TDS Version

July 2022