

Sand

Properties

Type: Latex wall paint, based on acrylic binder, added sand-like particles. Flügger Sand paint is a special wall paint that provides a surface with a rustic, fine-plastered look. When tinted, the colour will be darker than the same colour tinted in traditional latex wall paint.

Use

Suitable interior on walls where a surface with a rustic, fine-plastered look is desired, e.g. in offices, living rooms and corridors.

The substrate must be clean, dry, solid and suitable for being painted.

Cleaning before repainting should be made with Fluren 37, Basic Cleaner.

Slightly chalking or absorbent surfaces should be primed with Flügger Sealer.

The best result is obtained if the substrate is painted with traditional latex wall paint in the same colour as Flügger Sand, before applying Flügger Sand.

Stir before use.

Application with a wide brush in all directions or in circle movements depending on the desired effect.

Can also be applied with short-piled roller followed by processing with wide brush to obtain the correct effect.

Do not apply on areas bigger than can be processed with brush in wet paint.

Apply 2 coats to obtain the best result.



Please note!

OBS! It is recommended to make a sample draw-down until technique and result are satisfactory.

Storage: Cool, frost-free and tightly closed

Technical Data

Product Type	Acrylic paint
Gloss	5;Matte
Density (kgs/l)	1,64
Solids Weight %	67
Solids Vol. %	46
Nominal spreading rate (m ² /ltr.)	5
Min. working temp. during application and drying/curing	Min. +5°C
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Must not be diluted
Cleaning of Tools etc.	Water

Current TDS Version

September 2006

Replaces TDS Version

January 2003